

AZEK™ ADHESIVE

- Water-based, non-toxic, easy cleanup.
- Perfect for AZEK to AZEK adhesion.
- Glued joints will never open.



Size	Qty	Code
16oz	EA	1AZE08

FRANKLIN™ WATERPROOF TITEBOND® II WOOD GLUE

New water proof Titebond® II is the new generation of wood glues that are formulated with a unique polyaliphatic resin polymer called Duracet™ XTII. This polymer offers woodworkers better performance than original Titebond®, plus the Type II water resistance has unsurpassed heat resistance, sands easier, sets faster and is paintable. Easy water clean up, plus it is freeze thaw stable. Excellent for all porous materials.



Size	Qty	Code
8oz	EA	92GX08
16oz		92GX16
1GAL		92GX1G

TITEBOND III ULTIMATE WOOD GLUE

Titebond III Ultimate Wood Glue offers the best possible performance in woodworking glues. This waterproof formula provides superior bond strength, longer open assembly time and lower application temperature. The perfect choice for Interior and exterior woodworking.

- Passes ANSI/HPVA Type I water resistance.
- FDA approved for indirect food contact.
- Sands easily
- Water cleanup and non-toxic.



Size	Qty	Code
16oz	EA	92GU16
1GAL	EA	92GU1G

GORILLA™ PREMIUM GLUE

Easy to use. Incredibly strong. Will bond ceramics, plastics, metal, softwoods, hardwoods, teak and other woods without any special preparation or resin removal.

Gorilla™ Glue is an ideal all-purpose household glue. Along with its superior strength and versatility, consumers appreciate Gorilla™ Glues environmentally friendly, 100% solvent free formula. Carcinogen Free.



Size	Qty	Code
8oz	EA	92GG08
18oz		92GG18

ADHESIVES/CAULKS/WOOD PUTTIES

CONTACT CEMENT

Smooth spreading grade, maximum strength, waterproof, fast drying. Neoprene and resin formulation provides maximum strength and toughness. Permanently bonds laminates to wood, plywood, hardboard, metal, or plaster. Heat resistant and waterproof. Fast drying. Tan color.



Size	Qty	Code
1 GAL	EA	92ACON

MELAMINE GLUE "ROO-CLEAR"®

Melamine "Roo"® Glue is specifically made for bonding melamine coated boards. Makes butt joints stronger than the board's surfaces. Dries translucent (clear). Water based and non-toxic. 16 years in use; proven long term.



Size	Qty	Code
16oz	EA	92GM16
1 GAL		92GM1G

3M™ #90 AEROSOL ADHESIVE

Extra strength, industrial grade aerosol adhesive. Fast bonding action permits quicker handling of parts to speed assembly operations. Two-surface adhesive quickly and securely bonds difficult to hold materials such as laminates and polypropylene. The spray pattern directs the adhesive right where you want it. The adjustable spray tip lets you vary width and delivery rate.



Size	Qty	Code
16.5oz	EA	923M90

1–15 minute bonding range at room temperature. Resistance: 160°F. Translucent in color.

PL 400™ HEAVY-DUTY SUB-FLOOR ADHESIVE

PL 400™ construction adhesive is an indoor / outdoor synthetic rubber adhesive for bonding plywood subfloors to wood floor joists. This excellent field-applied adhesive makes a flooring system that is less expensive than non-glued systems and is stronger, stiffer and quieter.



Size	Qty	Code
10.2oz	EA	92PL10
29oz	EA	92PL29

PL 400™ can be used on all types of wood, treated lumber, ceramic tile, including subfloors, stair treads, slate floors, paneling, wood floors, furring strips, decks and patios, wallboard, and lap siding. VOC approved latex based.

DAP BUTYL-FLEX® GUTTER & FLASHING RUBBER ADHESIVE

Lasts up to 5 times longer than oil based caulks. No painting required. USDA authorized use for federally inspected meat & poultry plants. Meets Fed. Spec. TTS-001657, Type I, CID-A-A-272. Type III.



Size	Color	Qty	Code
10oz	White	EA	92CBUW

PHENOSEAL™ ADHESIVE CAULK

The phenolic-vinyl caulking adhesive rugged, permanently flexible, heat resistant and waterproof. Phenoseal™ bonds wood, tile, metal, glass, fiberglass, stone, almost any material to any other material. Forms wood joints stronger than wood itself. Does not crystallize or crumble. Completely unaffected by exposure to sunlight, salt, water, gasoline, oil, mild acids, and alkalis. Water based and environmentally safe.



Size	Color	Qty	Code
10oz	Transparent	EA	92CPHT
	White		92CPHW
	Dark Brown		92CPHR

DAP™ FIRE STOP SEALANT

- Classified for sealing around plumbing and wiring.
- Penetrates through fire rated walls and floors.
- One part silicone.
- Crack resistant.
- Non slumping.
- Not for fireplaces.



Size	Color	Qty	Code
			92CFIR

EXTEND HD SEALANT

- Extend DH is a thermoplastic sealant comprised of flexible rubbers and resins. It offers excellent adhesion to most building materials and It's exterior performance is enhanced by a stabilizer package to resist U.V. degradation.
- For use on Fiber Cement siding.
 - OSB
 - Vinyl
 - Pressboard
 - Metals
 - Hardboard
 - Siding



Size	Color	Qty	Code
10.5oz	White	EA	92CEXT

DAP™ "230" SEALANT

Silicone performance with latex offer ease of use. It is the first latex sealant to withstand 50% total joint movement. Outperforms silicone in overall performance. Permanent adhesion, lifetime flexibility and 50 year durability. Paintable. Water cleanup. Every color meets the performance requirements of Fed. Spec. TT-S-00230C, Type II, Class A.



Size	Color	Qty	Code
10.5oz	White	EA	92C23W
	Alum Grey		92C23G
	Bronze		92C23B

ADHESIVES/CAULKS/WOOD PUTTIES

SIKAFLEX-1a™

Sikaflex-1a is a 1 component, moisture-cured, non-sag, permanently flexible polyurethane sealant that is self-priming with most construction materials. It has demonstrated excellent resistance to aging and weathering in varied climates around the world. It resists attack from dilute acids and alkalines, jet fuel, water, and residential sewage. Curing to a flexible consistency with exceptional cut and tear resistance, Sikaflex-1a™ offers superior performance when used between elements with dissimilar coefficients of expansion: concrete, wood, glass, steel, aluminum, copper, ceramics, brick, asbestos, cement, polyester and epoxy.



Size	Color	Qty	Code
10.3oz	White	EA	92CSEW
	Bronze		92CSEB
	Grey		92CSEG
	Tan		92CSET
	Black		92CSEBL

SUPRESS ACOUSTICAL SEALANT

Use Supress Acoustical Sealant at panel edges and around any cut-outs for electrical boxes, pipes, sprinklers, etc.



Size	Qty	Code
29oz	EA	4007SL

DOW CORNING™ SILICONE SEALERS

With a limited lifetime warranty, the 100% silicone sealant protects and seals with 100% silicone rubber. Waterproof and weatherproof. Won't crack, crumble or dry out. Meets Red. Spec. TT-S-001543A, Class A. Meets requirements of FDA Regulation Number 21 CFR 177.2600. CID-A-A-272. Type IV.



Size	Color	Code
10.1oz	Clear	92CSIL

LEXEL®


The ultra-clear caulk in a see-through tube. New technology beyond silicone. It's clearer, tougher, and stronger than silicone. Firmly binds to almost any surface. Paintable and mildew resistant. Available in clear and white.



Size	Color	Qty	Code
10.5oz	Clear	EA	92CLXC
	White		92CLXW

ALEX PLUS™ ACRYLIC LATEX WITH SILICONE

Superior quality, moisture/mildew resistant caulk. Lasts for 25 years or more. Paintable. USDA authorized for federally-inspected meat and poultry plants. Exceeds ASTM. C-834-76, CID-A-A-272, Type II.



Size	Color	Qty	Code
10.1oz	Almond	EA	92CLAL
	Black		92CLBL
	Brown		92CLBR
	Cedar Tan		92CLCE
	Clear		92CLCL
	Slate Gray		92CLSG
	White		92CLWH

BLACK JACK FIBERED PLASTIC ROOF CEMENT, WET OR DRY

Waterproof. Forms a tight, strong seal. As easy to use on dry as damp surfaces.



Size	Qty	Code
1GAL	EA	93WET1
5GAL		93WET5
10oz tube		93WET2

PROTECTO SEALANT 25XL POLYURETHANE WINDOW AND DOOR INSTALLATION SEALANT

Protecto Sealant 25XL is a high performance, low modulus, one-component, moisture curing, polyurethane sealant. Protecto Sealant 25XL is a waterproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds. Protecto Sealant 25XL is used exclusively with the new Protecto Sill Drainage System.



Size	Color	Qty	Code
11oz	White	EA	92CPS25

Features

- 100% compatible with Protecto Wrap window and door sealing tape
- Aggressive adhesion to a variety of window substrates including wood, vinyl and aluminum
- Provides a strong, durable, weather resistant bond to most building substrates
- Mold and UV resistive
- Fast cure and solvent free formulation
- Excellent long-term weather resistance
- Meets AAMA and ASTM sealant standards

DEVCON'S TRIMBONDER™

AZEK Trimboards has aligned with Devcon, a leading industrial adhesive manufacturer, in the promotion of their unique two-part structural acrylic adhesive "TrimBonder".

TrimBonder is a perfect solution to filling nail holes and gaps in AZEK applications. TrimBonder can also be used to join sections on AZEK products together or to



Qty	Case Qty	Code
EA	6	92CAZEK
EA	10	92NAZEK

bond AZEK material to other substates. Applied with a regular caulk gun, TrimBonder is durable, permanent, UV stable, waterproof, and can withstand harsh weather without shinking, discoloring or yellowing. An adhesive that permanently bonds AZEK Trimboards, metals, wood, and PVC.

Applications

- Fills nail holes
- Fills gaps & joints
- Bonds all AZEK Trimboard products

Features

- Fits standard caulking gun
- Easily sands & paints well
- UV stable & waterproof

ADHESIVES/CAULKS/WOOD PUTTIES

CAULKING GUNS

Economy ratchet style guns with enamel finish to fit standard size tubes.



Size	Length	Qty	Code
11oz	9"	EA	92CG11
30oz	13.5"	EA	92CG30

QUIKRETE® NO.9902 CONCRETE BONDING ADHESIVE (LATEX)

Penetrates pores of old concrete, forming a chemical bond for new concrete. Roughing old surfaces is unnecessary.



Size	Qty	Code
1qt	EA	91WAD11
1GAL	EA	91WAD12

JIFFY SEAL CAULK J.S.-160H MASTIC

- SBS rubber modified.
- Heavy duty, cold applied bituminous coating.



Size	Color	Qty	Code
10.5oz		EA	91JS160

JIFFY SEAL MEMBRANE PRIMER #80

- #80 primer is an asphalt base primer for use on all horizontal applications above 40°F.
- Coverage is 125-225 sq. ft.



Size	Color	Qty	Code
1GAL		EA	91JS80

JIFFY SEAL MEMBRANE PRIMER #100

- #100 primer is a high tack SBS rubber base primer.
- It is used on all vertical surfaces before application of membrane and on all surfaces with temperatures between 25°F and 40°F.
- Coverage is 125-225 sq. ft.



Size	Color	Qty	Code
1GAL		EA	91JS90

ADHESIVES/CAULKS/WOOD PUTTIES

DUROCK™ ADHESIVE

Water-based mastic for ceramic and mosaic tile installation on interior walls. High strength, water-resistant, non-slip formula for use on wallboard, wonderboard, exterior grade plywood, hardboard and masonry surfaces. Easy trowelability and clean-up.



Size	Qty	Code
1QT	EA	94TTIQ
1GAL		94TTIG

TEC EZ LEVEL TA323

- Self leveling underlayment.
- Pourable, Latex-modified self-leveler. Ideal for large areas.
- For ceramic, natural stone, marble tile, carpet, and wood.
- Pour, pump, squeegee, or gaged spreader.
- Interior use.
- Must use TA 861 primer. See instructions.



Size	Code
50lb sack	92ATEC

TEC SURFACE PREP & PRIMER TA 861

- Acrylic latex based primer and patch additive.
- Improves adhesion and bond strengths and flexural strengths.
- Provides freeze/thaw resistance.
- Approved for exterior use.
- Must be used with EZ Level compound TA323.
- Covers 300–500 sq. ft.



Size	Code
1GAL	92ATEC1

DAP™ FAST'N FINAL® ALL-PURPOSE

Specially formulated for outdoor use. Lightweight. One fill, no sanding. Won't crack or shrink. Repairs stucco, concrete, brick and wood.



Size	Qty	Code
1QT	EA	92ASPA

DAP™ KWIK FOAM® INSULATING SEALANT

A one component, moisture cure, polyurethane foam insulation that expands to economically fill and seal large cavities. It stops air infiltration and will not degrade or shrink. Kwik Foam® contains a flame retardant and meets Montreal Protocol 1987.



Size	Qty	Code
20oz	EA	90FOAM

ADHESIVES/CAULKS/WOOD PUTTIES

DOW GREAT STUFF® BIG GAP FILLER SEALANT

Triple expanding polyurethane insulating foam sealant with a straw applicator. Fills, seals and insulates gaps, cracks and holes greater than 1/2 inch. Cures rigid. Cream color foam.



Size	Qty	Code
20oz	EA	90FOAM1

DOW GREAT STUFF® GAPS & CRACKS SEALANT

Minimal expanding polyurethane insulating foam sealant with a straw applicator. Fills, seals and insulates gaps, cracks and holes up to 1/2 inch. Cures rigid. Cream color foam.



Size	Qty	Code
20oz	EA	90FOAM2

DOW GREAT STUFF® WINDOW & DOOR SEALANT

Minimal expanding low-pressure formulation flexible polyurethane foam sealant with a straw applicator. Perfect for sealing window and door frame openings. Also ideal for sealing areas where low-pressure flexible foam is desirable. Cures flexible. Yellow color foam.



Size	Qty	Code
12oz	EA	90FOAM3

FIXALL®

FIXALL® is used to repair cracks and holes in plaster, gypsum wallboard and wood surfaces. It has high compressive strength and, therefore, makes an excellent floor under-layment for patching and leveling prior to installation of resilient floor-coverings. In addition, it can be used for models and in molds.



Size	Qty	Code
4.5#	EA	92AFIX
25#	EA	92AFIZ

WOOD PATCH

An all purpose highly effective plastic putty for wood repair. Accepts all stains and finishes. Patches hole and surface cracks in all woods.



Size	Color	Qty	Code
4oz	Birch	EA	WF006B
4oz	Maple		WF006M
4oz	Red Oak		WF006O
4oz	Redwood		WF006R
4oz	White		WF006W
16oz	Birch		WF012B
16oz	Maple		WF012M
16oz	Red Oak		WF012O
16oz	Redwood		WF012R
16oz	White		WF012W

ADHESIVES/CAULKS/WOOD PUTTIES

COLOR PUTTY

Makes wood finishing easier. Stain wood (if necessary), seal or varnish, fill nail holes and imperfections with correct shade of color putty. Finish with coat of seal or varnish (except epoxy). 3.68oz jars.



Size	Color	Qty	Code
1LB	White	EA	WF16WH
	Lt Birch		WF16LB
	Lt Oak		WF16LO

COLOR FILL KIT

- Laminate floor repairer and joint filler.
- Repairs chips and scratches.
- No mixing required.
- Includes solvent.



Size	Color	Qty	Code
	Beech Black	EA	6FGFA11
	Beech Plank		6FGFA12
	Blue		6FGFA13
	Green		6FGFA15
	Maple		6FGFA17
	White Oak		6FGFA19
	Alder		6FGFA20
	White Beech		6FGFA21
	Merbau		6FGFA23
	Pine		6FGFA24
	Red Oak		6FGFA25
	Cherry		6FGFA26

STAR® FIL-STIK®

Easy to use, semi-hard Fil-Stik®. Repairs minor scratches and nicks. Simply rub in and wipe off. Made to be finished over with lacquers, enamels, varnishes, or simply buffed.



Size	Color	Qty	Code
	Med Walnut	EA	WF17WA
	Dark Brown		WF17BR
	Red Mahogany		WF17BM
	Cherry Vale		WF17CH
	Natural		WF17NA
	Heritage Oak		WF17OA
	Off-White		WF17WH

BONDO® ALL PURPOSE WOOD FILLER

Repairs cracks, refills holes, patches and seals. Good for wood, concrete, brick, metal, stone, sheetrock and plastic.



Size	Qty	Code
1QT	EA	WF4000
1GAL		WF4010

GOOP-ON®

The modern wood, hole and crack filler. Stainable and sandable; can be used on exteriors as well as interiors. Will adhere to metal, glass, plaster, wood, furniture, etc. Perfect for new and unfinished floor installations.



Size	Qty	Code
1GAL	EA	6FM0GI