

# EPOXY

## BORA-CARE®

For use in and around homes, apartments, garages, museums, public and private institutions, schools, hotels, hospitals, kennels, stables, form buildings, trucks, trailers, warehouse, supermarkets, restaurants, and food processing plants.



For prevention and control of:

- Termites
- Carpenter Ants
- Wood Destroying Beetles
- Decay Fung

Size	Code
1qt	WCBC00

## RESTOR-IT™ EPOXY FILLER

Badly deteriorated wood and missing wood fiber can now be repaired with Restor-It™ Flexible Epoxy Filler. Gaps, cracks, holes and any missing portion of wood can be filled and re-used, eliminating the need to replace existing wood.

Once Restor-It™ Flexible Epoxy Filler is applied and cured, wood surface becomes usable again. Maximum adhesion bonds wood back together providing a sandable, nailable, drillable, carvable surface ready to paint, stain or varnish.

Restor-It™ protects wood in all temperatures and weather conditions. Surface readily accepts oil based primers, top coats and water-based latex paints.



Size	Code
2PT kit	WR2000
1GAL kit	WR2001

## RESTOR-IT™ EPOXY SEALER (PART A&B)

Turns soft, rotted wood hard and usable again. Stops rot and other damage from spreading.



Size	Code
2qt kit	WR1000

**RESTOR-IT™ EPOXY CLEANUP SOLVENT**



Size	Code
1PT can	WR3000

**SIMPSON ET 22 EPOXY ADHESIVE**

Advantages:

- Easy to use: gel consistency allows horizontal or vertical use.
- Reduced shrinkage: shrinkage during cure is from 1% to 2%.
- Moisture resistant: a chemical anchor that is resistant to hydrolyzation.
- Corrosion protection: ET compound seals the hole and encapsulates the embedded portion of the threaded rod.



Size	Code
22oz	9ET220

Installation:

- ET may be installed in concrete, brick or masonry. Check for proper mixture, a uniform gray color, before using. ET will not form an adhesive bond when dispensed as black or white.
- Codes: ICBO NO. 4945; SBCCI 94145; City of L.A. NO. RR25120, RR 25185 (ET22 and ET56.)



Gun	Code
	9EDT22



Nozzle & Nut	Code
	9EMN22



Brushes	Code
	99CC06

**SIMPSON SET PAC™ EPOXY-TIE ADHESIVE**

- For use in base material 45°F to 100°F.
- Works with standard caulking gun.
- Mixes with an electric drill.
- ICBO Building Code listed.



Size	Code
10oz	9SETPA